

CLAIMS

- Sub
A₄
- 5
- 10
- 15
- 20
- 25
- 30
1. A plate for printing comprising:
a mask with an opening area and a non-opening area;
a plate framework with at least four sides, on which said mask is fixed;
and
a paste removing member.
 2. The plate for printing according to Claim 1,
wherein said paste removing member is so structured as to have a flat
area and a slanting area.
 3. The plate for printing according to Claim 1,
wherein said paste removing member is disposed on said mask's non-
opening area.
 4. The plate for printing according to Claim 1,
wherein said paste removing member is disposed on a printing start side
or on a side opposite to said printing start side thereof.
 5. The plate for printing according to Claim 1,
wherein said paste removing member is disposed on a printing start side
and a side opposite to said printing start side, respectively.
 6. The plate for printing according to Claim 1,
wherein said paste removing member is disposed on a side of said plate
framework that is perpendicular to squeegee's forward moving direction.
 7. The plate for printing according to Claim 6,
wherein said paste removing member is formed in a one-piece structure
with a side of said plate framework.
 8. The plate for printing according to Claim 7,
wherein a spacing between said paste removing member and said side of
said plate framework is sealed with resin and the like.
 9. The plate for printing according to Claim 1,
wherein a degree of surface smoothness of said paste removing member is
equal to or higher than a degree of surface smoothness of said mask.
 10. The plate for printing according to Claim 1,

wherein a coefficient of friction of said paste removing member is smaller than that of said mask.

11. The plate for printing according to Claim 1,

wherein a length of said slanting area is made same as or longer than squeegee's thickness.

12. The plate for printing according to Claim 1,

wherein a slanting angle of said slanting area is made almost same as an angle complementary to squeegee's printing angle.

13. A plate for printing comprising:

a mask with an opening area and a non-opening area;

a plate framework with four sides, on which said mask is fixed;

and

a paste removing member formed of a flat area and a slanting area, both together constituting a side of said plate framework that is perpendicular to squeegee's moving forward direction.

14. A method of printing a paste on an object to be printed with said paste by means of said plate for printing according to Claim 1, comprising a step of removing a paste located at squeegee's non-printing side by means of said paste removing member before printing is started.

15. The method of printing a paste according to Claim 14,

wherein a squeegee is lowered in position, and is brought into contact with and slid on said paste removing member, respectively.

16. The method of printing according to Claim 14,

wherein said paste is Newtonian or dilatant.

17. The method of printing according to Claim 14,

wherein said object to be printed with said paste is prepared by laminating a mask film on both surfaces of a board, respectively, and also by forming a through hole therein; and said paste is filled in said through hole by said printing method.

18. The method of printing a paste according to Claim 14,

wherein said printing is performed by using a plate for printing that has said paste removing member at both printing start side and side opposite

Sub
B3
cont

to said printing start side, respectively, and by means of two squeegees of moving forth and moving back.

19. The method of printing according to Claim 14,

wherein said paste is formed of a metallic powder, a thermosetting resin and a curing agent and exclusive of a solvent.

5

20. A plate for printing that has a paste removing member disposed in such a way that at least a moving back squeegee passes said paste removing member when two squeegees of moving forth and moving back are used in printing a paste.

Sub
A5

20250701 09:19:01